

### General Features

- Oxygen recombination technology: maintenance-free.
- The patent grid alloy: less gassing, low self-discharging.
- Special paste formula: additives for deep discharge, long cycle life.
- High quality AGM separator: extend cycle life and prevent micro short circuit.
- The patent Nano silica gel electrolytes: improve the deep discharge performance.
- Cast on strap (COS) welding technology for high consistency and reliability.
- ABS container: increase the strength of battery.




### Application

- Electric vehicle
- Lawn mowers
- Illumination light
- Wheelchairs
- Sweeper
- Solar Kits
- Electric tools
- Golf trolley and golf cart

### Specification

Battery Model	5106-0009 12V3.4AH	
Capacity (25°C)	20HR (10.5V)	3.4Ah
	10HR (10.5V)	3.1Ah
	5HR (10.5V)	2.8Ah
	1HR (19.6V)	2.08Ah
Dimensions	Length	134mm
	Width	67mm
	Height	60mm
	Total Height	66mm (inc. terminals)
Approx. Weight	1.3Kg (2.87 lbs) ±5%	
Internal Resistance	Full charged at 25°C : ≤55mΩ	
Self Discharge	3% of capacity declined per month at (20°C)	

### Terminal Unit:mm



### Dimension Unit:mm

