

Pull T24 Speed


24V Premium Sliding Gate Operators



Made in AUSTRIA



FAST & RELIABLE OPERATION



INCLUDED
HEIGHT ADJ.
BASE PLATE



Residential Application



Steel gearing in oil bath



Easy to read LC Display, visible through the motor cover



Intelligent operator with encoder, eliminating limit switches



Automatic obstacle detection, gate reverses upon obstruction



Easy to use manual release, operated via a standard key




Standard soft start & stop for smooth operation



Excellent for solar applications



Encoder for precision



Oil bath, hardened steel gears



	Motor Power	Max Gate Leaf	Duty Cycle	Pinion	Pinion Height	Part Number
Pull T24 - Z16	24V	600 Kg @ 216mm/sec	80%	Z16	105mm	1555-0020
> With separate transformer						1555-0021
Pull T24 - Z20		500 Kg @ 270mm/Sec		Z20	113mm	1556-0008
> With separate transformer						1556-0022
Pull T24 - Z24		400 Kg @ 325mm/Sec		Z24	121mm	1555-0028
> With separate transformer						1555-0029

All kits include Height Adjustable Base Plate and Power Lead

POPULAR ACCESSORIES



Iris Photobeams Safety Device
#1059-0070



Tousek Radio Gear Plug-in Receiver & 2x 2 button transmitters
#1018-0133



2AH Backup Battery Allows emergency egress
#5106-0027



Range Increasing Antenna 433MHz Aerial With Bracket & 5m Of Coax Cable
#6049-0326

1300 366 046

sales@global-access.com.au

For more information, visit our website!

global-access.com.au

