

24VDC
Solar Friendly

700kg

325mm per sec

INCLUDED HEIGHT ADJ. MOUNTING PLATE

LCD Digital Display

Switch-Mode Power Supply

Display Visible Cover

Built-in Encoder

Easy to use Euro-Key manual release

3 YEAR WARRANTY

MADE IN AUSTRIA

316mm
307mm
207mm

OPTIONAL TOUSEK RADIO GEAR

1018-0133

OPTIONAL 24H BACKUP BATTERY

5106-0022



Oil bath gear box with hardened, machine cut steel gearing for maximum reliability



During a power failure, the operator can be run in emergency mode via the optional battery backup kit



Intelligent, self-learning with encoder as standard eliminates the need for limits makes for a fast, easy installation



Intelligent Sensor and Automatic Reversal System (ARS) increases safety



Inbuilt LCD Digital display allows for easy programming, and the ability to display the last 800 events for easy diagnosis

PULL T24 MODELS	MOTOR-POWER SUPPLY	MAX. GATE WEIGHT	MAX. GATE WIDTH	MAX SPEED	DUTY CYCLE	PINION	PINION HEIGHT	PLUS BASE PLATE	PART NO.
PULL T24 - Z16 > With Separate Transformer	24V	600kg	30m	13m/min 216mm/sec	80%	Z16	99mm	105mm	1556-0020 1556-0021
PULL T24 - Z20 > With Separate Transformer	24V	400kg	30m	16.25m/min 270mm/sec	80%	Z20	107mm	113mm	1556-0008 1556-0022
PULL T24 - Z24 > With Separate Transformer	24V	300kg	30m	19.5m/min 325mm/sec	80%	Z24	115mm	121mm	1555-0028 1555-0029

OPTIONAL ACCESSORIES TO ENHANCE YOUR PULL T AUTOMATION

Tousek Plug-in Relay Output Module	Light OR Status	CHOOSE ONE ONLY	Tousek Pull T Plug-in Relay Output Module, 24V/2W			1018-0102
Tousek Plug-in Gate Status Module						1018-0101

