

SWING X - For gates up to 500Kg



GENERAL ADVANTAGES AT A GLANCE:

- Self-locking gearing
- Euro-key emergency manual release
- Integrated speed sensor
- Adjustable soft stop, both open and close
- Adjustable internal, mechanical stops
- Supplied with control board in separate enclosure

| SWING X MODELS | | INPUT VOLTAGE | MOTOR PHASE | MAX. LEAF WEIGHT | MAX. LEAF WIDTH | MAX. FORCE | WORKING STROKE | DUTY CYCLE | SINGLE KIT PART NO. | DOUBLE KIT PART NO. |
|----------------|--|---------------|-------------|------------------|-----------------|------------|----------------|------------|---------------------|---------------------|
| X3 HD | | 230V | 1~ | 500 kg | 3m | 4,000N | 320mm | 60% | 1616-0025 | 1616-0026 |
| X4 HD | | 230V | 1~ | 500 kg | 4m | 5,000N | 320mm | 60% | 1616-0028 | 1616-0029 |
| X4 LHD | | 230V | 1~ | 500 kg | 4m | 5,000N | 450mm | 60% | 1616-0025 | 1616-0026 |
| X5 LHD | | 230V | 1~ | 500 kg | 5m | 6,500N | 450mm | 40% | 1616-0028 | 1616-0029 |

OPTIONAL MODULES TO ENHANCE YOUR SWING X AUTOMATION

| | | |
|------------------------------------|---|-----------------------|
| E-Lock/Magnet Module | Magnet output for open and closed positions | 1018-0088 |
| Courtyard Lamp/Control Lamp Module | For 230V lamp connection, Max. 100W | 1044-0014 |
| External Gate Status Module | Potential free signal contacts, Max. 24V, 10W | 1018-0087 |
| 2.5M OR 10M Cable Connecting Kit | Suits the Swing X TP | 6049-0611 6049-0612 |
| Connection Box Incl Fittings | Suits the Swing X3 TP & Swing X4 LH | 6049-0613 |
| Bolt-on Post Bracket | Bracket - Post Side - Bolt On - Stainless Steel | 6049-0610 |



Quality metal gears



Visible enclosure display



Inbuilt mechanical stops



Euro-key manual release



Large spindle & sprocket



Adjustable both opening & closing directions

Soft-stop function



ARS (Automatic Reverse System)